



Unit 1, Allandale Business Park, cnr
Morkel & Le Roux Road, Midrand,
Gauteng, South Africa
www.sensablesensors.co.za
email: sales@sensable sensors.co.za
Tel: +(27) 11 205 0082

16-18 Monte Carlo Road,
Mahogany Ridge, Pinetown,
KwaZulu-Natal, South Africa
www.sensablesensors.co.za
email: sales@sensable sensors.co.za
Tel: +(27) 31 700 8260

DorTag VI OEM Stand Alone Proximity System



SINGLE DOOR ACCESS CONTROL SYSTEM

- *Motorized Gates & Doors*
- *Parking Applications*
- *Apartment Blocks*
- *Personnel Access Control*

The controller can be placed in a secured location; and run one or two readers (max 15m shielded cable earthed to ground) from the controller.

FEATURES

- Up to 1000 Users
- Master Tag programming
- Two Reader Head Capability
- Auto Exiting Software
- Programmable Relay Output (150ms – 9S)
- Entire Memory/Single User Voiding
- Push Button Exit Input
- Fire Alarm Input
- Last Tag Read Display

SPECIFICATIONS

OPERATING VOLTAGE	12/24 V AC/DC
AVERAGE CURRENT CONSUMPTION	33 mA
MAXIMUM CURRENT CONSUMPTION	55mA @ 12V
RELAY OUTPUT RATING	24/5A Change over contacts
OPERATING FREQUENCY	125 KHZ
READ RANGE	6cm – 10cm (Dependent on tag type)
READER HEADS	1 or 2
READER HEADS FEEDER CABLE	5 Core 0.5m Standard to a 2m length Special, 5m max (if unshielded). 15m max (if shielded).
MECHANICAL DIMENSIONS	Controller -104mm(L) x 94mm(W)x 25mm(D) Reader Head – 75mm(L) x 39mm(W) x 15mm(D)
OPERATING TEMPERATURE	-10°C to +60°C
INDICATIONS	Visual – Bi Color LED Audible - Buzzer
ENVIRONMENTAL RATING	IP00
Mass	Controller- 70g Reader Head – 70g

(The Company reserves the right to amend product specifications and information without notice.)

PLEASE CONTACT OUR SALES TEAM for further information.

**PART OF THE MARANTEC COMPANY GROUP - OPENING DOORS IN SOUTHERN AFRICA
PROUD SUPPORTERS AND SUPPLIERS OF:**

